

HYUNDAI

PRODUCT DATA SHEET Lubricants – Industrial

Converging the best and the most optimal, with incomparable power, enhancing performance at an amazing rate, **HYUNDAI XTeer** created by Hyundai's built-up technology will open the new world of Industrial lubricants.

XTeer Brake Fluid

Description

XTeer Brake Fluid is an extra high performance hydraulic brake fluid for use in automotive disc, clutch systems. XTeer Brake Fluid meets or exceeds the requirement of FMVSS No. 116.

It has high consistent, safe brake performance under severe braking pressure because of high boiling point and reduces leakage, loss of fluid because of minimum rubber component swelling.

Also, It has extended life and reliability of brake system components.

Application

- ◇ Automotive brake system(disc, drum), anti-skid brake system and clutch system.

Features / Benefits

- ◇ It has high performance in severe environment(mountain offload, downhill)
- ◇ Prevent vapor locking situation
- ◇ Extended life and reliability of brake system components

Typical Properties

Item	Unit	DOT-3	DOT-4
Kinematic Viscosity,-40°C	cSt	1051	1057
Kinematic Viscosity, 100°C	cSt	2.0	2.3
Boiling point, Dry	°C	248	258
Boiling point, Wet	°C	146	163
pH		8.82	8.94